

United States Patent [19]

Briere et al.

[11] Patent Number: 5,968,560

[45] Date of Patent: Oct. 19, 1999

[54] BLOW MOLDING DEVICE FOR PRODUCING THERMOPLASTIC CONTAINERS

[75] Inventors: Dominique Briere, Le Havre; Léon Colisy, Saint Martin du Manoir; Paul La Barre, Sainte Adresse; Pascal Santals, Le Havre, all of France

[73] Assignee: Sidel, Le Havre, France

[21] Appl. No.: 08/945,089

[22] PCT Filed: Apr. 16, 1996

[86] PCT No.: PCT/FR96/00576

§ 371 Date: Oct. 17, 1997

§ 102(e) Date: Oct. 17, 1997

[87] PCT Pub. No.: WO96/33059

PCT Pub. Date: Oct. 24, 1996

[30] Foreign Application Priority Data

Apr. 19, 1995 [FR] France 95 04651

[51] Int. Cl.⁶ B29C 49/56; B29C 33/30

[52] U.S. Cl. 425/192 R; 425/195; 425/522; 425/541; 249/102

[58] Field of Search 425/183, 192 R, 425/195, 522, 541; 249/102

[56] References Cited

U.S. PATENT DOCUMENTS

467,881	1/1892	Fisher	249/102
1,409,591	3/1922	Schavoir	249/102
3,191,225	6/1965	Polka	425/541
3,753,641	8/1973	Turner et al.	425/541
3,784,344	1/1974	Korsch	425/526
3,871,611	3/1975	Taketa	249/102
4,072,456	2/1978	Appel et al.	425/183
5,262,116	11/1993	Von Holdt, Sr.	425/192 R
5,288,222	2/1994	Wieser	425/192 R

5,332,384	7/1994	Abramat	425/522
5,346,386	9/1994	Albrecht et al.	425/541
5,358,396	10/1994	Giesen	425/192 R

FOREIGN PATENT DOCUMENTS

2057196	5/1971	France	249/102
2613979	10/1988	France	.
2646802	11/1990	France	.
2653058	4/1991	France	425/522
3613543	12/1986	Germany	.
3934495	12/1990	Germany	.

OTHER PUBLICATIONS

"Quick-change systems add to blow molders' market reach", by Patrick A. Toensmeier, Modern Plastics International, Aug. 1991 (pp. 30-31).

Patent Abstracts of Japan, vol. 12, No. 286 (M-727), Aug. 5, 1988, (Abstract of Japanese reference 63-062,710 dated Mar. 19, 1988).

Primary Examiner—Robert Davis

Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] ABSTRACT

The invention concerns a device for producing thermoplastic containers, in particular bottles, by the blow-molding or stretch blow-molding of a preheated preform. The device comprises at least one mould consisting of two half-moulds (2) each supported by a mould carrier, the two mould carriers being movable relative to each other. Each half-mould (2) comprises a shell holder (9), supported by the respective mould carrier, and a shell (7) which is equipped with a half-impression (8) of the container to be obtained and can be rendered integral in a detachable manner with its shell holder (9) by rapid-fastening means (19-23). The shell (7) and the shell holder (9) are of complementary shapes such that they contact each other at least partially for heat conduction purposes whilst the pipes and connections for circulating and/or heating fluids are provided in the shell holder alone.

14 Claims, 3 Drawing Sheets

